

Benchtop • Low Speed • Ventilated • Centrifuge

T6-S



Scan to watch product video



6000 rpm	Maximum Speed
4387 xg	Maximum RCF
24x15 ml	Maximum Capacity
≤55dB (A)	Noise Level(dBA)

Technical Specifications:

Time range	0-99minutes 59s	Speed accuracy	±10rpm
Acceleration /Deceleration rates	0--9	Display	LCD
Power supply	AC220V,50HZ,5A,170W	Motor	Frequency Converter motor
Dimension	420x320x240mm(LxWxH)	Weight without rotor	18kg

Matched Rotors

No.	Rotor	Capacity	Max.speed	Max. RCF	Note
NO.1 	Angle rotor	12×5-10-15ml	6000r/min	4387xg	PC/PP tube
	Adapter	12×2ml			Vacuum blood collection tubes
NO.2 	Angle rotor	6×50ml	5000r/min	3354xg	PC/PP tube bottom
	Adapter	6×15/10ml			PC/PP tube
	Adapter	6×5ml			Vacuum blood collection tubes
NO.3 	Angle rotor	18×5-10ml	4500r/min	2717xg	PC/PP tube / Vacuum blood collection tubes
	Adapter	18×2ml			Vacuum blood collection tubes
NO.4 	Angle rotor	24×15ml	4000r/min	2160xg	PC/PP tube / Vacuum blood collection tubes
	Adapter	24×2ml			Vacuum blood collection tubes