

PRP&PRF&CGF · Centrifuge

TPRP6-S



Scan to watch product video



6000 rpm

Maximum Speed

4387 xg

Maximum RCF

6x50 ml

Maximum Capacity

≤50dB (A)

Noise Level(dBA)

- * Easily switch between RPR, CGF, APRF, and IPRF protocols.
- * Versatile variable-speed setting.
- * Compatible with 30ml/20ml10ml injection syringes or blood collection tubes and 30ml/20ml/10ml/8ml/5ml PRP tubes.

Technical Specifications:

Time range	1-99minutes 59s adjustable	Speed accuracy	±10rpm
Power supply	AC220V,50HZ,5A,150W	ACC/DEC	1-10rates
Dimension	430x320x250mm(LxWxH)	Weight without rotor	18kg

Matched Rotors

No.	Rotor	Capacity	Max.speed	Max. RCF	Note
NO.1 	Angle rotor	12x15/10/5ml	6000r/min	4387xg	PP/PC tube
NO.2 	Angle rotor	6x50ml	4000r/min	2268xg	Injection syringe or PRP tube
	Adapter	6x30/20ml			PP/PC tube
	Adapter	6x10ml			PP/PC tube
	Adapter	6x5ml			PP/PC tube
NO.3 	Angle Rotor	8x8/10ml	3300r/min	1339xg	CGF special rotor and program